LIQUID RELEASE



STAMP-TOOL RELEASING AGENT

DESCRIPTION

LIQUID RELEASE is a liquid-release agent designed for use with THIN-CRETE stamped overlay systems and anywhere powdered release agents are impractical to use. This release agent conditions the stamping tool and prevents it from sticking to concrete allowing for the best possible imprint without pulling up the surface. **LIQUID RELEASE** is odorless and leaves minimal residue on the concrete surface.

FEATURES/BENEFITS

- No dust
- Colorless
- · Clean tool release
- Will not damage stamps
- No residue

PACKAGING

LIQUID RELEASE is available in 1 gal (3.8 L) and 5 gal (18.9) units.

SHELF LIFE

4 Years in original, unopened container.

COVERAGE

Coverage is approximately 200 ft²/gal (4.9 m²/L).

DIRECTIONS FOR USE

APPLICATION PROCESS:

LIQUID RELEASE should be sprayed lightly on the under-side of the stamping tool. Before stamping, the concrete or overlay should be allowed to reach an initial set--a spongy but firm surface that is not hard. Once the concrete is stamped, remove the stamping tool immediately but carefully and allow the concrete surface to dry. Reapply LIQUID RELEASE as needed throughout stamping process.

FINISHING:

Because LIQUID RELEASE leaves no color, ANTIQUING AGENT may be used to create a secondary color to the stamped surface. Consult technical data sheets for application procedures and safety precautions.

PRECAUTIONS/LIMITATIONS

- For professional use only.
- In all cases, consult the SDS before use.

